

## POLYMAT VARIOSEAL PN

### SEMI-AUTOMATIC CONTACT HOT SEALING DEVICE,

suitable for: sealing of containers made of plastic and glass.



#### FEATURES

- Perpendicular V2A sealing stamp
- Electro-pneumatic, high compression pressure (e.g. for glass sealing)
- Pressure control
- Continuous height adjustment

The digital control system integrated into the system provides ultimate operating ease, e.g.

- Temperature control with target/current value comparison
- Sealing time setting
- 4 selectable operating programmes
- Production number (per hour / total)
- Error message

#### ELECTRICAL CONNECTIONS

- Power supply: 230 V
- Grid frequency: 50/60 Hz
- Nominal current: 2,5 A
- Power consumption: 1 KW
- Compressed air connection: min. 5 bar
- Air consumption: 6 m<sup>3</sup>/h

#### SEAL PARAMETERS

- Seal stamp: 100x100 mm
- Seal lift: 25 mm
- Sealing force: approx. 1,5 kN
- Sealing time: 0,5 – 10 sec
- Sealing temperature: 100 – 300°C
- Sealing capacity: approx. 500 h/ h

#### DIMENSIONS

- (W x D x H): 350 x 550 x 740 mm
- Weight: 30 kg



**Handing ApS™**  
 Nordkranvej 5-9, Vassingerød  
 DK - 3540 Lyngbe  
 Tel.: +45 48160166  
[www.handing.dk](http://www.handing.dk)

### Polymat-Varioseal PN

Dette dokument er vejledende.  
 Der tages forbehold for fejl.  
 This document is only guiding.  
 We make reservation for possible errors.  
 Copyright © By Handing ApS. All Rights Reserved.

Alle mål i mm.  
 All measures in mm.

Lager nr. /NNJ

**F914**