

# Collamat® 3600

## technical data



Collamat®	3610
• Operational width	95 mm (3 3/4 in)
• Max. feeding speed	20 m/min. (6 ft/min.)
• Labeling accuracy	± 1 mm (1/25 in)
• Minimal label length	10 mm (10/25 in)
• Max. Label reel diameter	350 mm (14 in)
• Drive	2 phase stepping motor
• Control	16 bit microprocessor
• Voltage	115-230 V / 50-60 Hz / 110
• Approbation	CE



**Handing ApS™**  
 Nordkranvej 5-9, Vassingerød  
 DK - 3540 Lyngø  
 Tel.: +45 48160166  
 www.handing.dk

### Collamat 3610

Dette dokument er vejledende.  
 Der tages forbehold for fejl.  
 This document is only guiding.  
 We make reservation for possible errors.  
 Copyright © By Handing ApS. All Rights Reserved.

Alle mål i mm.  
 All measures in mm.

Lager nr. /TN

**F917**

# Collamat® 3600

## technical data

**Collamat® 3600 for Cost-efficient  
and User-oriented Labeling**

Collamat® labeling systems manufactured by Collamat Stralfors AG are made according to the latest state-of-the-art technology. Modern technology is being used when developing any label applicator so to optimize the product. In the low-cost range, Collamat® 3600 is characterized by a variable speed adjustment, a high-precision label-

ling capacity and an easy-to-use operator panel. A small price for top results, indeed.

### Exact Adjustments

Collamat® 3600 was specially developed for applications with low or medium-range conveying speeds and designed for the fully automated processing of adhesive labels off coils. Of course, the system may also be used for semi-automatic processing.

Depending on the task on hand, speeds may be freely selected between 3 and 20 meters per minute. Application performance is at a high feeding precision of  $\pm 1$  millimeter.

### Easy Handling

All operating processes are simple, safe, and timesaving due to the compact design and synoptical operator panel, including a mains

switch, a signal lamp and three potentiometers for continuous adjustment to the required speed, the adjustment of the optoelectronic label scanning device, plus the setting of the predispensing unit.



*High-precision labeling accuracy: Collamat® 3600 offers a labeling accuracy of  $\pm 1$  mm. ( $\pm 1/25$  in)*



**Handing ApS™**  
Nordkranvej 5-9, Vassingerød  
DK - 3540 Lyngø  
Tel.: +45 48160166  
www.handing.dk

### Collamat 3610

Dette dokument er vejledende.  
Der tages forbehold for fejl.  
This document is only guiding.  
We make reservation for possible errors.  
Copyright © By Handing ApS. All Rights Reserved.

Alle mål i mm.  
All measures in mm.

Lager nr. /TN

**F917**