



**Range of Application**

Mixing, homogenizing and dyeing of powdery or granulated components in the plastics, chemical, chemico-technical industry, drug and dye works, food and luxury food industry as well as textile and leather industry. Moreover special purposes such as dissolving solids in liquids, polishing metal or plastic parts, moving inert media to avoid structural changes and cleaning containers by means of solvents.

**Advantages**

- Intensive mixing even in the case of small quantities for example of additives or active substances
- Well suitable for small and frequently changing quantities of product
- Easy exchanging of the mixing container
- Easy cleaning of the mixing container
- Drum hoop also usable as a conveying roll for short distances

**Operation**

The container rotating around an inclined axis serves as a mixing tool. The rotating movement and the inclined arrangement of the container walls result in a mixing effect which is based on the combination of gravity and frictional forces. The particles are lifted and slide or fall back into the product to be mixed. This guarantees intensive mixing.

**Additional equipment**

All drum hoop mixers can be equipped with a protective fence according to the EC directives and with a three-blade mixing insert for accelerating and improving the mixing intensity.

**Technical Data**

Type	Material	Drum Hoop		Roller Track			Roller Track + Drum Hoop		Rolls	Axle Distance
		D	B3	L	B2	B1	H	Weight Roller Track Drum Hoop		
RRM 200	stainless steel	1080	453	1000	500	1020	1300	80 kg 24 kg	90	500

Type	Volume		Charge limit max.	Drum Hoop Speed min <sup>-1</sup> min <sup>-1</sup>	Power kW	Voltage Volt	Speed min <sup>-1</sup>	Frequency Hz.	Enclosure ip
	gross	net							
RRM 200	200 l	150 l	120 kg	21	0,55	230/400	250	50	54

**Range of Application**

For accelerating and improving the mixing intensity of powdery and dry products.

**Operation**

The mixing insert is put on the bottom of the drum and fastened at the drum wall by parallel locking. It is easily exchangeable due to the draw and turn locking.

**Mixing Inserts**

(suitable for the following drums; if desired, they can be adapted to containers provided on site)

Drum size	Diameter in mm	Height in mm	Material thickness in mm	Material	Weight in kg
200 l	560	882	1,5	1.4541	7,0

**Drums**

Gross Volume	Diameter in mm	Height in mm	Beadings	Material	Weight in kg
200 l	560	882	yes	1.4541	18,1

- mixing, homogenizing, dyeing
- 5 different sizes
- mixing containers for 50 up to 300 liters
- batch operation

- wide range of additional equipment and special executions
- variable speed
- optional with ATEX conformity acc. to regulation 94/9 EG



**Handing ApS™**  
Nordkranvej 5-9, Vassingerød  
DK - 3540 Lyngby  
Tel.: +45 48160166  
www.handing.dk

**200 liter  
Tromleblander**

Dette dokument er vejledende.  
Der tages forbehold for fejl.  
This document is only guiding.  
We make reservation for possible errors.

Copyright © By Handing ApS. All Rights Reserved.

Alle mål i mm.  
All measures in mm.

Lager nr. /LH

**R1166**